



AMPLIN

LINEAR HIGH BAY

The IKIO Amplin Linear High Bay is designed for a variety of applications and mounting heights. Wide-angle optics, multiple lumen packages and color temperatures make it ideal for industrial, commercial, manufacturing, gymnasium, and other applications that utilize traditional linear fluorescent and HID fixtures. Suggested mounting heights are between 15-25 feet. This high bay reduces up to 70% of the energy usage and has a life span of over 10 years. This fixture is available in a frosted lens.

Application : Ideal for Industrial Applications; Manufacturing Facilities, Warehouses, Gymnasiums, Athletic Facilities, Workshops, and Large Areas.

FEATURES

- **Exceptional efficacy** (Up to 150 lm/W).
- **75,000 hours** of life time.
- **Superior heat dissipation** capability due to use of multiple heat sinks.
- **Sleek design and low-profile** makes it suitable for a wide range of applications.
- **Smooth and uniform light output** with no flickering or humming.
- **Savings of up to 75%** over conventional fluorescent fixtures.
- **In-built surge protection (5 kV)** helps keep the voltage in check.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PRODUCT ORDERING DETAILS

AMPLIN LINEAR HIGH BAY - 2FT - 0-10V DIMMING

POWER	SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
75 W	662187544380	AMPLIN LINEAR HIGH BAY : 75.85 W / 10800 LM / 5000 K / 100-277 V / WHITE	•	142.38 lm/W	225 W	View / Download
100 W	662187477978	AMPLIN LINEAR HIGH BAY : 100.2 W / 14577 LM / 5000 K / 100-277 V / WHITE	•	145.54 lm/W	300 W	View / Download
150 W	662187477985	AMPLIN LINEAR HIGH BAY : 145.8 W / 21709 LM / 5000 K / 100-277 V / WHITE	•	148.9 lm/W	450 W	View / Download

AMPLIN LINEAR HIGH BAY - 4FT - 0-10V DIMMING

POWER	SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
200 W	662187478005	AMPLIN LINEAR HIGH BAY : 198.7 W / 29235 LM / 5000 K / 100-277 V / WHITE	•	147.1 lm/W	600 W	View / Download
240 W	662187478012	AMPLIN LINEAR HIGH BAY : 236.3 W / 33896 LM / 5000 K / 100-277 V / WHITE	•	143.43 lm/W	720 W	View / Download
300 W	662187478029	AMPLIN LINEAR HIGH BAY : 303.5 W / 44685 LM / 5000 K / 100-277 V / WHITE	•	147.24 lm/W	900 W	View / Download

ACCESSORIES

INCLUDED IN THE BOX

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187476049	IK-ACC-ARC	SUSPENSION CABLE KIT (2 Pcs / High Bay)	View / Download

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187557700	IK-OCCS-B	IK-OCCS-B : HD406VRH-D : Microwave Smart Sensor (Color Black)	View / Download
662187558097	IK-OCCS-W	IK-OCCS-W : HD406VRH-D : Microwave Smart Sensor (Color White)	View / Download
662187558073	IK-OCCS-REMOTE	IK-OCCS-R: HD03R - Microwave Smart Remote	View / Download
662187528601	IK-EMH-18170-FY	EMERGENCY PACK FOR LED FIXTURE 18W/90 MIN/SPLIT TYPE/L	View / Download
662187558875	IK-10W-ED	EMERGENCY PACK FOR LED FIXTURE 10W/90 MIN/SPLIT TYPE/L	View / Download

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.