

CPS Series

DELPHI LINEAR LOW BAY

CPS SERIES | LINEAR LOW BAYS



PRODUCT DETAILS

IKIO's Delphi Linear Low Bay — an energy efficient replacement for traditional fluorescent tubes — comes with excellent CCT & Power selectable capabilities. It allows customers to select different CCTs & wattages, thereby offering greater flexibility when it comes to application areas. Moreover, the luminaire's superior design helps in rendering smooth and evenly distributed light output with no dark areas.

FEATURES

- **Incorporates advanced technology** - CCT & power selectable capabilities for greater light control.
- **Quick and hassle-free installation.**
- **Energy saving technology** - saves greater energy over the traditional lighting fixtures.
- **High performing luminaire** - smooth and evenly distributed light output with no dark areas.
- **Flexibility of application** - suitable for multiple applications because of its low profile and CCT & Power selectable feature.

APPLICATIONS



Large Warehouses

Schools

Underground Parking

Commercial Buildings

Lots Walkways

Mezzanine Floors

WARRANTY & QUALIFICATIONS*



DesignLights Consortium® (DLC) qualified product (Premium). Not all versions of this product may be DLC Qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

**Warranty and Qualifications can vary per item / SKU, see technical data sheets (TDS) for specific information.*

PRODUCT ORDERING DETAILS

ORDERING PART NUMBERS

- # **IK-SLO2R** (For 2 ft)
- # **IK-SLO4R** (For 4 ft)
- # **IK-SLO8R** (For 8 ft)

QUALIFIED PART NUMBERS

- # **IK-SLO2R (15/18/22/25) W** (For 2 ft)
- # **IK-SLO4R (30/36/40/50) W** (For 4 ft)
- # **IK-SLO8R (60/68/72/80) W** (For 8 ft)

100-277 V FIXTURES

2' FIXTURES

POWER SELECTABLE (RANGE)	SKU CODES	DESCRIPTION	DLC	CCT SELECTABLE (RANGE)	EFFICACY	LUMENS	BEAM	AVG. LIFE HOURS	CASE
15 W-18 W-22 W-25 W	662187528298	DELPHI LINEAR LOW BAY: 15-18 W-22 W-25 W / 3500 K / 4000 K / 5000 K / Dimmable	★	3500 K-4000 K-5000 K	127 lm/W	1905 lm-2286 lm-2794 lm-3175 lm	120°	50,000	1

4' FIXTURES

POWER SELECTABLE (RANGE)	SKU CODES	DESCRIPTION	DLC	CCT SELECTABLE (RANGE)	EFFICACY	LUMENS	BEAM	AVG. LIFE HOURS	CASE
30 W-36 W-40 W-50 W	662187528304	DELPHI LINEAR LOW BAY: 30 W-36 W-40 W-50 W / 3500 K-4000 K-5000 K / Dimmable	★	3500 K-4000 K-5000 K	127 lm/W	3810 lm-4572 lm-5080 lm-6350 lm	120°	50,000	1

8' FIXTURES

POWER SELECTABLE (RANGE)	SKU CODES	DESCRIPTION	DLC	CCT SELECTABLE (RANGE)	EFFICACY	LUMENS	BEAM	AVG. LIFE HOURS	CASE
60 W-68 W-72 W-80 W	662187528328	DELPHI LINEAR LOW BAY: 60 W-68 W-72 W-80 W / 3500 K-4000 K-5000 K / Dimmable	★	3500 K-4000 K-5000 K	140 lm/W	7620 lm-8636 lm-9144 lm-10160 lm	120°	50,000	1

ACCESSORIES OPTIONALS

SKU CODES	DESCRIPTION	CASE
662187558875	EMERGENCY PACK FOR LED FIXTURE 10 W/90 MIN/SPLIT TYPE/L AC	1
662187528601	EMERGENCY PACK FOR LED FIXTURE 18 W/90 MIN/SPLIT TYPE/L DC	1
662187548487	HD401S-CR : SMART OCCUPANCY SENSOR ON/OFF ONLY	1
662187548043	HD407V-CR : SMART OCCUPANCY SENSOR WITH DAYLIGHT HARVESTING	1
662187477046	HD05R - REMOTE CONTROL	1
662187528342	ROPE CHAIN- HANGING CABLES SETS	1
662187477121	WALL MOUNT FOR 2 FT LINEAR LOW BAY	1
662187477138	WALL MOUNT FOR 4 FT LINEAR LOW BAY	1
662187477145	WALL MOUNT FOR 8 FT LINEAR LOW BAY	1
662187476711	WIRE GAURDS WITH CLIPS - 2 FT COMPTIBLE FOR CPS SERIES LINEAR LOW BAYS	1
662187476728	WIRE GAURDS WITH CLIPS - 4 FT COMPTIBLE FOR CPS SERIES LINEAR LOW BAYS	1

MOUNTING OPTIONS

	SKU CODES	DESCRIPTION	CASE
	662187476735	WIRE GAURDS WITH CLIPS - 8 FT COMPTIBLE FOR CPS SERIES LINEAR LOW BAYS	1
	662187548456	4 W EMERGENCY DRIVER	1

MOUNTING OPTIONS

	SKU CODES	DESCRIPTION	CASE
	662187472546	CHAIN MOUNT KIT	1