



PRODUCT DETAILS

IKIO's T5 Tube is designed in a way that it can easily replace the existing T5 fluorescent lighting in any commercial or residential space. In fact, its unique design creates a perfectly uniform visual appearance that cannot be distinguished from traditional fluorescent fixtures. The tube comes in various types (type A, type B, and type C). Alongside being an ideal LED solution for customers needing high light output, this tube helps save energy and has a long life span, resulting in attractive payback times and TCO (Total Cost to Operate) benefits.

FEATURES

- **Unique design** with a perfectly uniform visual appearance.
- Exceptional efficacy and light output with a wide beam no flickering.
- Low energy consumption and maintenance cost.
- High CRI helps the colors look crisp.
- Internal/external voltage driver options allow you to choose a T5 type best suited for your needs.
- The tubes are ballast compatible.

APPLICATIONS

Offices Schools

Retail Stores Residential Spaces

General Areas

WARRANTY & QUALIFICATIONS







*Warranty and Qualifications can vary per item/SKU, see technical data sheets (TDS)





PRODUCT ORDERING DETAILS (QUALIFICATION MODEL # IK-T504 (Size 4 FT, Efficacy - 160 lm/W))

100-277 V FIXTURES

POWER	SKU CODES	DESCRIPTION	DLC	FINISH	SIZE	CCT	EFFICACY	LUMENS	AVG. LIFE HOURS	BASE	CASE
15 W	662187534312	T5 TUBE TYPE B: 15 W / 2700 K / Non Dimmable		WHITE	4 ft	2700 K	160 lm/W	2400 lm	50,000		1
15 W	662187534336	T5 TUBE TYPE B: 15 W / 4000 K / Non Dimmable		WHITE	4 ft	4000 K	160 lm/W	2400 lm	50,000		1
15 W	662187548364	T5 TUBE TYPE B: 15 W / 5000 K / Non Dimmable		WHITE	4 ft	5000 K	160 lm/W	2400 lm	50,000		1
15 W	662187553764	T5 TUBE TYPE B: 15 W / 5000 K / Non Dimmable		WHITE	4 ft	5000 K	160 lm/W	2400 lm	50,000		1
18 W	662187534350	T5 TUBE TYPE B: 18 W / 2700 K / Non Dimmable		WHITE	4 ft	2700 K	160 lm/W	2880 lm	50,000		1
24 W	662187557410	T5 TUBE TYPE B: 24 W / 2700 K / Non Dimmable		WHITE	4 ft	2700 K	150 lm/W	3600 lm	50,000		1
24 W	662187547725	T5 TUBE TYPE B: 24 W / 5000 K / Non Dimmable		WHITE	4 ft	5000 K	150 lm/W	3600 lm	50,000		1